

ENGLISH STANDARD		Top Notch	Top Notch 9	Top Notch 7	Top Notch 1S	Top Notch FR	Top Gun	Top Gun 9	Top Gun 1S	Top Gun FR	Top Gun FR Lite	Top Gun Vision	Odyssey	Odyssey Lite	Odyssey FR	Odyssey Open	Softouch	Softouch SD
Width	in	60	60	60	60	60	62	62	60	62	62	62	64	64	64	64	60	60
Roll Size	yards	50	50	50	50	50	50	50	50	45	50	50	75	100	100	100	50	50
Weight	oz/yd ²	11.5	9.0	7.0	7.5	11.5	11.5	9.0	9.0	13.0	8.0	11.0	6.5	5.5	7.25	5.75	11.0	12.5
Tensile Tear	lbf; Warp x Fill	500+ x 460	500+ x 300	350 x 300	320 x 255	500 x 240	500+ x 388	360 x 250	480 x 340	498 x 380	275 x 200	255 x 150	297 x 220	200 x 190	300 x 240	300 x 215	348 x 222	368 x 268
Tongue Tear	lbf; Warp x Fill	46 x 38	40 x 32	35 x 27	29 x 25	24 x 14	40 x 32	30 x 29	38 x 30	25 x 18	12 x 10	34 x 15	22 x 20	20 x 13	12 x 12	14.5 x 12	36 x 30	61 x 54
Spray Rating		100	100	100	100	90+	90+	90+	90+	90+	90+	n/a	90+	90	90+	80	90+	100
3 Drop	cm	40	40	40	82	76	76	71	76	70	60	n/a	51	40	21	n/a	84	84
Warranty	years	10	9	8	5	8	8	7	7	8	5	5	3	1	3	3	3	5
Breathability	g/m ² /24 hour	645	700	625	260	170	116	100	180	92	78	631	87	95	86	890	90	96
Shrinkage	%; Warp x Fill	0 x 0	0 x 0	0 x 0	<1 x 0	0 x 0	0 x 0	0 x 0	0 x 0	0 x <1	<1 x <1	0 x 0	0 x <1	0 x <1	0 x <1	<1 x <1.25	<1 x <1	0 x 0
Stretch	%; Warp x Fill	<1 x <1	<1 x <1	<1 x <1	<1 x <1.5	<1 x <1	<1 x <1	<1 x <1	<1 x <1	<1 x <1	<1 x <1	2.5 x 2.5	<1 x <1	0 x <1	<1 X <1.25	<1 x <1.5	<1 x <1	<1 x <1
Taber Abrasion	Cycles till breakthrough	600+	600+	450	1,600+	2,000+	16,000+	10,000+	10,000+	16,000+	2,900+	16,000+	2,900+	2,500+	2,900+	900+	13,000+	13,000+
Roll Diameter	in	7.5	7.0	6.5	6.0	7.0	7.0	6.0	6.0	6.75	5.75	7	6.5	7.0	7.25	7.25	12.5	12.5
Approx. Weight of Roll	lbs	62	47/62	38	40	64	64/82	47	47	65	42	61/78	56	63	81	64	59	67
8" for 10 min	mls	0	0	0	0	0	0	0	0	0	0	n/a	0	0	0	n/a	0	0
Denier of base fabric		840	600	600	600	600	600	450	600	600	300	600	300	150x300	300	300	n/a	n/a