

METRIC		Top Notch	Top Notch 9	Top Notch 7	Top Notch 1S	Top Notch FR	Top Gun	Top Gun 9	Top Gun 1S	Top Gun FR	Top Gun FR Lite	Top Gun Vision	Odyssey	Odyssey FR	Odyssey Open	Softouch	Softouch SD
Width	meters	1.524	1.524	1.524	1.524	1.524	1.575	1.575	1.524	1.575	1.575	1.575	1.626	1.626	1.626	1.524	1.524
Roll Size	meters	45.72	45.72	45.72	45.72	45.72	45.72	45.72	45.72	41.01	45.72	45.72	68.36	91.14	91.14	45.72	45.72
Weight	grams/m ²	389.92	305.15	237.3	254.29	389.92	389.92	305.15	305.15	440.77	271.25	373.0	220.39	245.82	194.96	423.82	423.8
Tensile Tear	Newton; Warp x Fill	2,224+ x 2,046	2,224+ x 1,334	1,557 x 1,334	1,423 x 1,134	2,224+ x 1,068	2,2243+ x 1,726	1,601 x 1,112	2,135 x 1,512	2,215 x 1,690	1,223 x 890	1,134 x 667	1,321 x 979	1,334 x 1,068	1,334 x 956	1,548 x 988	1,637 x 1,192
Tongue Tear	Newton; Warp x Fill	205 x 169	180 x 142	155.7 x 120.1 27	129 x 111	107 x 62	178 x 142	133 x 129	169 x 133	111 x 80	53 x 44	151.2 x 66.7	98 x 89	53 x 53	64 x 53	160 x 133	271.3 x 240.2
Spray Rating		100	100	100	100	90+	90+	90+	90+	90+	90+	n/a	90+	90+	80	90+	100
3 Drop	cm	40	40	40	82	76	76	71	76	70	60	n/a	51	21	n/a	84	84
Warranty	years	10	9	8	5	8	8	7	7	8	5	5	3	3	3	3	5
Breathability	g/m ² /24 hour	645	700	625	260	170	116	100	180	92	78	631	87	86	890	90	96
Shrinkage	%; Warp x Fill	0 x 0	0 x 0	0 x 0	<1 x 0	0 x 0	0 x 0	0 x 0	0 x 0	0 x <1	<1 x <1	0 x 0	0 x <1	0 x <1	<1 x <1.25	<1 x <1	0 x 0
Stretch	%; Warp x Fill	<1 x <1	<1 x <1	<1 x <1	<1 x <1.5	<1 x <1	<1 x <1	<1 x <1	<1 x <1	<1 x <1	<1 x <1	2.5 x 2.5	<1 x <1	<1 X <1.25	<1 x <1.5	<1 x <1	<1 x <1
Taber Abrasion	Cycles till breakthrough	600+	600+	450	1,600+	2,000+	16,000+	10,000+	10,000+	16,000+	2,900+	16,000+	2,900+	2,900+	900+	13,000+	13,000+
Roll Diameter	cm	19.05	17.78	16.5	15.24	17.78	17.78	15.24	15.24	17.145	14.6	17.78	16.51	18.415	18.415	31.75	31.75
Approx. Weight of Roll	kilograms	28.123	21.3/28.12	17.2	18.144	29.030	29.03/37.2	21.319	21.319	29.483	19.05	27.7/35.4	25.401	36.741	29.030	30.391	30.4
8" for 10 min	mls	0	0	0	0	0	0	0	0	0	0	n/a	0	0	n/a	0	0
Denier of base fabric		840	600	600	600	600	600	450	600	600	300	600	300	300	300	n/a	n/a