

Acrylic Coated Flame Retardant Polyester



301 Caribbean Blue



315 Silver Gray



303 Sand



311 Black



309 White



319 Red*



305 Forest Green




Acrylic Coated Flame Retardant Polyester



606 Olive Drab



602 White



618 Silver Gray



635 Sand



Marlen Textiles





Odyssey FR is an acrylic coated, 100% woven flame retardant polyester fabric (300 denier) with a pad and topcoat. Odyssey FR meets many flame retardant specifications, both initial and leaching. That means that unlike other fabrics, you don't have to worry about still meeting a flame specification after it has been exposed to the elements. As part of the Odyssey family of economical coated fabrics, it is characterized by excellent strength, durability, tear and abrasion resistance, dimensional stability, UV and mildew resistance at an economical price point. Odyssey FR provides flame retardancy without the high cost and weight of heavier fabrics. Odyssey FR is perfect for awnings, air ducts, signs, banners, luggage, bags, tents, gazebos, canopies, or any application requiring flame resistance.

Odyssey FR, economical and flame retardant. Now that's hot.

Odyssey Open is an acrylic coated, 100% woven flame retardant polyester fabric (300 denier) with a pad coat. Its unique coating allows the fabric to be open, providing air and water permeability. Odyssey Open meets MVSS-302 to provide some flame retardancy. As part of the Odyssey family of economical coated fabrics, it is characterized by excellent strength, durability, tear and abrasion resistance, dimensional stability, UV and mildew resistance at an economical price point. Because of its unique construction, Odyssey Open is not for every application, but it is perfect for cots, air ducts, signs, banners, outdoor furniture or any other application requiring openness and flame resistance.

Odyssey Open, seeing through to the right fabric.

TECHNICAL DATA					
Characteristic	TOP NOTCH FR®	TOP GUN FR®	TOP GUN FR LITE®	ODYSSEY FR®	ODYSSEY OPEN®
Width, inches	60	62	62	64	64
Roll Size, yards	50	45	50	100	100
Weight, oz/yard²	11.5	13.0	8.0	7.25	5.75
Tensile (lbf), Warp x Fill	500 x 240	498 x 380	275 x 200	300 x 240	300 x 215
Tongue Tear (lbf), Warp x Fill	24 x 14	25 x 18	12 x 10	12 x 12	14.5 x 12
Spray Rating	90+	90+	90+	90+	n/a
3 Drop Rating (cm)	90	70	60	21	0
Warranty Period (years)	8	8	5	3	3
Shrinkage (%), Warp x Fill	0 x 0	0 x <1	<1 x <1	0 x <1	<1 x <1.25
Stretch (%), Warp x Fill	<1 x <1	<1 x <1	<1 x <1.25	<1 x <1.25	<1 x <1.5
Flame Retardant Specificatio	n				
MVSS-302	Х	Х	Х	Х	X
NFPA 701	Х	Х	Х	Х	
California State Fire Marshall	Х	Х	х	X	
CPAI 84	х	Х	Х	Х	
CAN/ULC-S109-03	Х	Х	х	X	
FAA/FAR 25.853	Х	Х	Х	X	



500 Orchard Street New Haven, MO 63068 (800) 343-6326 (573) 237-4444 Fax (573) 237-4491 www.marlentextiles.com